

An Optimized Design Framework for Compact 3D Monolithic Microwave Integrated Circuit Bandpass Filters Employing Meander Resonator Structures for 5G Millimeter-Wave Applications

Dr. Clara Neumann

Department of Software Engineering University of Cologne, Germany

Dr. Tobias Braun

Institute for Intelligent Systems University of Bonn, Germany

Published Date: -

12 June 2025,

Page No.: - 26-31

KEYWORDS

5G millimeter-wave, MMIC bandpass filter, meander resonator, 3D integration, coplanar waveguide, compact filter design, microwave circuits, optimization framework, RF systems, electromagnetic modeling.

ABSTRACT

The rapid evolution of fifth-generation (5G) communication systems has intensified the demand for highly compact, high-performance, and efficient millimeter-wave (mmWave) components. Among these, bandpass filters (BPFs) play a critical role in ensuring signal integrity, selectivity, and interference mitigation. This research presents an optimized design framework for compact three-dimensional (3D) monolithic microwave integrated circuit (MMIC) bandpass filters utilizing meander resonator structures. The study integrates advanced electromagnetic modeling, multilayer fabrication techniques, and design optimization strategies to achieve superior miniaturization and enhanced performance characteristics. The proposed framework incorporates meander-type resonators to reduce footprint while maintaining high Q-factor and selectivity, supported by analytical modeling and simulation-based validation. Comparative evaluation with existing MMIC and microstrip filter architectures demonstrates improvements in bandwidth control, insertion loss reduction, and stopband attenuation. The framework also explores the role of multilayer coplanar waveguide (CPW) structures and their interaction with 3D integration techniques. Results indicate that the proposed architecture effectively meets the stringent requirements of 5G mmWave systems. This work contributes to the advancement of scalable, high-density RF front-end design and provides insights into future integration of intelligent optimization techniques within microwave filter design.

1. Introduction

The proliferation of high-speed wireless communication technologies, particularly 5G, has necessitated the development of compact and high-frequency components capable of operating efficiently in the millimeter-wave spectrum. Bandpass filters are fundamental in RF front-end systems, enabling frequency selection and suppression of unwanted signals. However, conventional filter designs often face limitations in size, scalability, and performance when extended to mmWave frequencies (Rappaport et al., 2013).

The integration of monolithic microwave integrated circuits (MMICs) has emerged as a viable solution to address these challenges by enabling compact and high-

performance designs within a single semiconductor substrate (Robertson and Lucyszyn, 2001). Furthermore, the adoption of three-dimensional (3D) architectures allows for vertical stacking of components, significantly reducing footprint while enhancing electrical performance.

Meander resonator structures have gained attention due to their ability to achieve size reduction without compromising electrical characteristics. Their geometrical flexibility enables effective control of resonant frequency and coupling mechanisms (Belova-Ploniene et al., 2019). This makes them particularly suitable for mmWave filter design, where compactness and precision are critical.

The primary objective of this research is to develop an optimized framework for designing compact 3D MMIC bandpass filters using meander resonators. The study aims to bridge the gap between miniaturization and performance by integrating advanced modeling, multilayer design techniques, and optimization strategies. The scope includes theoretical modeling, structural design, performance evaluation, and comparative analysis with existing approaches.

2. Literature Review

The design of microwave bandpass filters has evolved significantly, with numerous approaches proposed to enhance performance and reduce size. Early work by Hong and Lancaster (1995, 1996) introduced microstrip-based resonator designs, laying the foundation for modern filter architectures. These designs, while effective, face limitations in compactness when scaled to higher frequencies.

Subsequent research focused on multilayer and coplanar waveguide (CPW) structures to improve integration density. Vo et al. (2006a, 2006b) demonstrated the feasibility of 3D CPW transmission lines and inductors in multilayer MMICs, highlighting the potential for vertical integration. Similarly, Sinulingga et al. (2016, 2018) explored modeling techniques for multilayer MMIC components, emphasizing the importance of accurate electromagnetic characterization.

Meander-type resonators have been extensively studied for their compact design capabilities. Belova-Ploniene et al. (2019) provided a comprehensive review of meander structures, identifying their advantages in miniaturization and flexibility. Nasution et al. (2021) further applied meander resonators in CPW-based bandpass filters, demonstrating improved compactness and performance.

Recent advancements have incorporated advanced resonator geometries and multi-band capabilities. Basit et al. (2022, 2023) introduced dual-band and UWB filters using novel resonator structures, achieving enhanced frequency selectivity. Zhang et al. (2023) extended this work by integrating multi-frequency suppression techniques for 5G applications.

In the context of mmWave systems, Feng et al. (2019) and Rao et al. (2022) developed high-frequency bandpass filters with improved selectivity and packaging techniques. However, these designs often face trade-offs

between size, performance, and fabrication complexity.

Despite these advancements, a significant research gap remains in integrating meander resonators within 3D MMIC architectures while maintaining optimal performance. This study addresses this gap by proposing a comprehensive design framework that combines structural innovation with performance optimization.

3. Methodology

3.1 Framework Overview

The proposed design framework integrates electromagnetic modeling, structural optimization, and multilayer MMIC design principles. It consists of three key stages: resonator design, 3D structural integration, and performance optimization.

3.2 Meander Resonator Design Principles

Meander resonators achieve miniaturization by folding transmission lines into compact geometries. The resonant frequency is determined by the effective electrical length, which can be adjusted through geometric parameters such as line width, spacing, and number of turns.

According to Belova-Ploniene et al. (2019), meander structures offer enhanced control over coupling and resonance characteristics, enabling precise filter tuning. In this study, parametric modeling is used to optimize these parameters for mmWave operation.

3.3 3D MMIC Integration

The integration of resonators into a 3D MMIC structure involves multilayer stacking using CPW-based interconnections. This approach reduces planar footprint while improving isolation and signal integrity.

Key design considerations include:

- Interlayer coupling effects
- Substrate material properties
- Via and interconnect optimization

The use of multilayer CPW structures, as demonstrated by Vo et al. (2006a), enables efficient signal propagation with minimal loss.

3.4 Electromagnetic Modeling and Simulation

Full-wave electromagnetic simulations are employed to analyze filter performance. The modeling incorporates:

- S-parameter analysis
- Frequency response evaluation
- Loss characterization

Advanced modeling techniques from Sinulingga et al. (2016) are utilized to ensure accurate representation of multilayer effects.

3.5 Optimization Strategy

The optimization process focuses on:

- Minimizing insertion loss
- Maximizing return loss
- Enhancing selectivity

Iterative simulation and parameter tuning are used to achieve optimal performance. The framework also allows for integration of machine learning-based optimization in future extensions.

3.6 Functional Workflow

The design process follows a systematic workflow:

1. Initial resonator design
2. Parameter optimization
3. 3D integration
4. Performance validation

This structured approach ensures consistency and scalability in filter design.

4. Results / Findings

The implementation of the proposed framework yields significant improvements in filter performance. The designed 3D MMIC bandpass filter demonstrates a compact footprint with reduced size compared to traditional planar designs. The use of meander resonators enables effective miniaturization while maintaining high

selectivity.

Simulation results indicate a low insertion loss and high return loss within the desired mmWave frequency band. The filter exhibits sharp roll-off characteristics, ensuring efficient suppression of out-of-band signals. Compared to existing designs such as those by Feng et al. (2019), the proposed filter achieves comparable or improved performance with reduced physical dimensions.

The multilayer integration enhances signal isolation and reduces parasitic effects, contributing to overall performance stability. Additionally, the framework allows for flexible tuning of frequency response through parameter adjustments.

The results validate the effectiveness of combining meander resonator structures with 3D MMIC architectures for 5G applications.

5. Discussion

The findings highlight the potential of meander-based 3D MMIC filters in addressing the challenges of modern RF systems. The integration of compact resonator structures within multilayer architectures enables significant size reduction without compromising performance. This aligns with the observations of Belova-Ploniene et al. (2019), who emphasized the efficiency of meander structures in compact designs.

From a theoretical perspective, the study demonstrates the importance of electromagnetic coupling and resonance control in achieving desired filter characteristics. The use of CPW-based multilayer structures further enhances performance by minimizing losses and improving signal integrity.

However, certain trade-offs must be considered. The complexity of 3D integration increases fabrication challenges, particularly in maintaining precision at mmWave frequencies. Additionally, thermal management and material limitations may impact long-term reliability.

Compared to existing approaches, the proposed framework offers a balanced solution between compactness and performance. While designs by Basit et al. (2023) focus on multi-band capabilities, the present work emphasizes structural optimization for mmWave applications.

The framework also opens avenues for incorporating artificial intelligence techniques for automated optimization, aligning with emerging trends in RF design.

6. Conclusion

This research presents a comprehensive framework for designing compact 3D MMIC bandpass filters using meander resonator structures for 5G mmWave applications. The study successfully integrates theoretical modeling, structural design, and performance optimization to achieve high-performance filter characteristics.

The proposed approach addresses key challenges in miniaturization and integration, demonstrating improved efficiency and scalability. The findings contribute to the advancement of next-generation RF front-end systems and provide a foundation for future research in intelligent microwave design.

Future work may focus on experimental validation, fabrication techniques, and integration with machine learning-based optimization frameworks to further enhance performance and adaptability.

References

1. A. Ashley and D. Psychogiou, "X-Band quasi-elliptic non-reciprocal bandpass filters (NBPFs)," *IEEE Transactions on Microwave Theory and Techniques*, vol. 69, no. 7, pp. 3255–3263, Jul. 2021, doi: 10.1109/TMTT.2021.3081021.
2. A. Basit, A. Daraz, M. I. Khan, N. Saqib, and G. Zhang, "Design, modeling, and implementation of dual notched UWB bandpass filter employing rectangular stubs and embedded l-shaped structure," *Fractal and Fractional*, vol. 7, no. 2, Art. no. 112, Jan. 2023, doi: 10.3390/fractalfract7020112.
3. A. Basit, M. I. Khattak, M. Al-Hasan, J. Nebhen, and A. Jan, "Design and analysis of a compact GSM/GPS dual-band bandpass filter using a t-shaped resonator," *Journal of Electromagnetic Engineering and Science*, vol. 22, no. 2, pp. 138–145, Mar. 2022, doi: 10.26866/jees.2022.2.r.70.
4. A. R. Nasution, E. P. Sinulingga, and A. H. Rambe, "Multilayer coplanar waveguide bandpass filter based on meander resonator," in 2021 5th International Conference on Electrical, Telecommunication and Computer Engineering, *ELTICOM 2021 -Proceedings*, Sep. 2021, pp. 47–49, doi: 10.1109/ELTICOM53303.2021.9590118.
5. B. Yang, Z. Yu, J. Lan, R. Zhang, J. Zhou, and W. Hong, "Digital beamforming-based massive MIMO transceiver for 5G millimeter-wave communications," *IEEE Transactions on Microwave Theory and Techniques*, vol. 66, no. 7, pp. 3403–3418, Jul. 2018, doi: 10.1109/TMTT.2018.2829702.
6. D. Belova-Ploniene, V. Slegeryte, D. Plonis, and A. Katkevicius, "Applications and design methods of meander-type structures: A review," in *Proceedings of 2019 IEEE Microwave Theory and Techniques in Wireless Communications, MTTW 2019*, Oct. 2019, pp. 82–86, doi: 10.1109/MTTW.2019.8897246.
7. D. W. Astuti, R. R. Putra, Muslim, and M. Alaydrus, "Substrate integrated waveguide bandpass filter for short range device application using rectangular open loop resonator," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 11, no. 5, pp. 3747–3756, Oct. 2021, doi: 10.11591/ijece.v11i5.pp3747-3756.
8. E. P. Sinulingga, "Modelling and characterisations of wideband coplanar waveguide MMIC components for nano-scale device applications," PhD Thesis, The University of Manchester, 2014.
9. E. P. Sinulingga, A. A. Rezazadeh, and P. B. Kyabaggu, "3D momentum modeling technique and measurements of CPW compact GaAs multilayer MMICs," in *Asia-Pacific Microwave Conference Proceedings, APMC*, Dec. 2016, vol. 2, doi: 10.1109/APMC.2015.7413232.
10. E. P. Sinulingga, A. R. Nasution, and P. B. Kyabaggu, "Perturbation effect on a dual mode CPW multilayer MMIC bandpass filter," in 2019 3rd International Conference on Electrical, Telecommunication and Computer Engineering, *ELTICOM 2019 -Proceedings*, Sep. 2019, pp. 66–69, doi: 10.1109/ELTICOM47379.2019.8943907.
11. E. P. Sinulingga, P. B. K. Kyabaggu, C. D. Sedayu, and A. A. Rezazadeh, "Characterization of low impedance 3d coplanar waveguide interconnects for compact MMICs," *IOP Conference Series: Materials*

- Science and Engineering, vol. 309, no. 1, Art. no. 12070, Feb. 2018, doi: 10.1088/1757-899X/309/1/012070.
12. G. Zhang, A. Basit, M. I. Khan, A. Daraz, N. Saqib, and F. Zubir, "Multi frequency controllable in-band suppressions in a broad bandwidth microstrip filter design for 5G wi-fi and satellite communication systems utilizing a quad-mode stub-loaded resonator," *Micromachines*, vol. 14, no. 4, Art. no. 866, Apr. 2023, doi: 10.3390/mi14040866.
 13. I. D. Robertson and S. Lucyszyn, Eds., *RFIC and MMIC design and technology*. Institution of Engineering and Technology, 2001, doi: 10.1049/pbcs013e.
 14. J. Lu, "Design and characterization of GaAs multilayer CPW components and circuits for advanced MMICs," Ph.D. Thesis, Faculty of Science and Engineering, The university of Manchester, London, 2011.
 15. J. S. Hong and M. J. Lancaster, "Couplings of microstrip square open-loop resonators for cross-coupled planar microwave filters," *IEEE Transactions on Microwave Theory and Techniques*, vol. 44, no. 11, pp. 2099–2109, 1996, doi: 10.1109/22.543968.
 16. J. S. Hong and M. J. Lancaster, "Microstrip bandpass filter using degenerate modes of a novel meander loop resonator," *IEEE Microwave and Guided Wave Letters*, vol. 5, no. 11, pp. 371–372, 1995, doi: 10.1109/75.473539.
 17. K. Chang and L. Hsieh, *Microwave ring circuits and related structures*. Wiley, 2004, doi: 10.1002/0471721298.
 18. L. H. Hsieh and K. Chang, "Simple analysis of the frequency modes for microstrip ring resonators of any general shape and correction of an error in the literature," *Microwave and Optical Technology Letters*, vol. 38, no. 3, pp. 209–213, Jun. 2003, doi: 10.1002/mop.11017.
 19. L. T. Phuong, B. Journet, and D. B. Gia, "A microwave active filter for nanosatellite's receiver front-ends at s-bands," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 9, no. 2, Art. no. 973, Apr. 2019, doi: 10.11591/ijece.v9i2.pp973-981.
 20. M. A. Sazali, N. A. Shairi, and Z. Zakaria, "Hybrid microstrip diplexer design for multi-band WiMAX application in 2.3 and 3.5 GHz bands," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 8, no. 1, pp. 576–584, Feb. 2018, doi: 10.11591/ijece.v8i1.pp576-584.
 21. M. N. Hushim, N. A. Wahab, T. S. A. T. M. Zin, and N. Ghazali, "Inter-connected coupled lines resonator topology for bandpass filter application," *International Journal of Electrical and Computer Engineering (IJECE)*, vol. 10, no. 3, pp. 2523–2534, Jun. 2020, doi: 10.11591/ijece.v10i3.pp2523-2534.
 22. Q. Sun, V. T. Vo, J. Tan, Davies, and A. A. Rezazadeh, "Miniaturized multilayer CPW pHEMT amplifiers," in *2008 European Microwave Integrated Circuit Conference, EuMIC 2008*, Oct. 2008, pp. 44–47, doi: 10.1109/EMICC.2008.4772224.
 23. R. N. Simons, *Coplanar waveguide circuits, components, and systems*. Wiley, 2001, doi: 10.1002/0471224758.
 24. T. Gokdemir et al., "Multilayer passive components for uniplanar Si/SiGe MMICs," in *IEEE MTT-S International Microwave Symposium Digest*, 1997, vol. 2, pp. 761–764, doi: 10.1109/mwsym.1997.602901.
 25. T. S. Rappaport et al., "Millimeter wave mobile communications for 5G cellular: It will work!" *IEEE Access*, vol. 1, pp. 335–349, 2013, doi: 10.1109/ACCESS.2013.2260813.
 26. V. T. Vo, L. Krishnamurthy, Q. Sun, and A. A. Rezazadeh, "3-D low-loss coplanar waveguide transmission lines in multilayer MMICs," *IEEE Transactions on Microwave Theory and Techniques*, vol. 54, no. 6, pp. 2864–2871, Jun. 2006, doi: 10.1109/TMTT.2006.875458.
 27. V. T. Vo, L. Krishnamurthy, Q. Sun, and A. A. Rezazadeh, "Miniature CPW inductors for 3-D MMICs," in *IEEE MTT-S International Microwave Symposium Digest*, Jun. 2006, pp. 1377–1380, doi: 10.1109/MWSYM.2006.249507.

28. V. V. Tyurnev, "Coupling coefficients of resonators in microwave filter theory," Progress in Electromagnetics Research B, vol. 21, no. 21, pp. 47–67, 2010, doi: 10.2528/pierb10012103.
29. W. Feng et al., "28-GHz high-selectivity bandpass filters with dual-behavior resonators using GaAs technology," IEEE Transactions on Plasma Science, vol. 47, no. 12, pp. 5277–5282, Dec. 2019, doi: 10.1109/TPS.2019.2950708.
30. Y. Rao, H. J. Qian, J. Zhou, Y. Dong, and X. Luo, "Miniaturized 28-GHz packaged bandpass filter with high selectivity and wide stopband using multilayer PCB technology," IEEE Microwave and Wireless Components Letters, vol. 32, no. 6, pp. 664–667, Jun. 2022, doi: 10.1109/LMWC.2022.3163613.