
UHF RFID Sensing and Localization Architectures for Internet of Things Driven Food Safety, Retail Intelligence, and Intelligent Transportation Systems

Hugo Pereira

Department of Electrical and Information Engineering, University of Granada, Spain

Published Date: - 28 Mar 2026, Page No.: - 42-50

KEYWORDS

UHF RFID, Internet of Things, food quality sensing, indoor localization, vehicular tracking, retail analytics.

ABSTRACT

Radio Frequency Identification technology has evolved far beyond its original role as a simple identification and tracking mechanism and now occupies a central position in the development of large scale Internet of Things ecosystems. The convergence of UHF RFID sensing, localization, and communication has enabled a new class of cyber physical infrastructures that operate with minimal power, extreme scalability, and high economic efficiency. This research article presents a comprehensive theoretical and empirical synthesis of UHF RFID based sensing and localization systems for food quality monitoring, retail analytics, and intelligent transportation systems. Drawing exclusively on peer reviewed scientific literature and established technical references, the article develops a unified conceptual framework that explains how RFID sensors, localization algorithms, vehicular identification systems, and neural assisted signal processing models combine to create robust and intelligent IoT platforms.

The work begins by establishing the foundational role of RFID in the Internet of Things, highlighting how object level connectivity transforms traditional data acquisition into continuous environmental intelligence as proposed by Ashton and later expanded by Jia and Feng. The article then extends into the physical layer, explaining how biopolymer based RFID sensors provide flexible, sustainable, and chemically sensitive interfaces for monitoring food freshness and environmental conditions as demonstrated by Saggin and colleagues. From this material foundation, the study advances into spatial intelligence, detailing how interference based three dimensional localization, angle of arrival estimation, antenna diversity, and support vector regression enable high resolution tracking of both tagged and untagged objects within complex indoor and vehicular environments. Special emphasis is placed on transportation systems, where RFID enabled tolling, vehicle identification, and lane monitoring create a real time traffic intelligence infrastructure that supports both safety and efficiency. The article integrates research on RFID based vehicular localization, magnetic loop hybrids, and gate control systems driven by convolutional neural networks to demonstrate how RFID has evolved into a decision making sensor network rather than a passive data carrier. Theoretical and practical trade offs related to duty cycle limitations, synchronization, industrial IoT constraints, and extreme environment deployment are critically analyzed to establish the operational boundaries of these systems.

By synthesizing sensing, localization, machine intelligence, and regulatory frameworks into a single analytical narrative, this article contributes a unified theoretical model for UHF RFID based IoT platforms. The findings demonstrate that RFID technology, when augmented by modern signal processing and neural inference, forms the backbone of scalable, low energy, and high reliability cyber physical systems capable of supporting the future of food safety, retail automation, and intelligent transportation networks.

INTRODUCTION

The modern Internet of Things represents one of the most transformative paradigms in contemporary engineering and information science. It redefines the boundary between the physical world and the digital domain by enabling everyday objects to become active participants in data generation, communication, and decision making. At the heart of this transformation lies Radio Frequency Identification technology, which has progressed from a niche tracking solution into a foundational infrastructure for large scale cyber physical systems. The early conceptualization of the Internet of Things by Ashton framed RFID as the technological bridge that allows physical items to speak to digital networks, thereby shifting computation from being human centered to object centered (Ashton, 2009a; Ashton, 2009b). This philosophical shift remains as relevant today as when it was first articulated, but its technological expression has become vastly more complex and powerful.

The proliferation of RFID has been driven not merely by its capacity to identify objects but by its ability to support sensing, localization, and communication in a single low power platform. Unlike conventional wireless sensor networks that require batteries and complex networking protocols, passive and semi passive RFID tags derive energy from reader signals and operate with minimal infrastructure. This makes them uniquely suited to the massive scale envisioned by the Internet of Things, where billions of objects must be monitored without unsustainable energy and maintenance costs (Jia et al., 2012; Valhouli, 2010). The convergence of RFID with sensing and computation transforms it into a ubiquitous interface between the physical environment and digital intelligence.

Food safety, retail automation, and transportation systems represent three of the most economically and socially critical domains where this convergence is taking place. In the food supply chain, the ability to monitor freshness, temperature, humidity, and chemical changes in real time is essential to reduce waste, prevent contamination, and protect public health. Saggin et al. demonstrated that flexible

biopolymer based RFID sensors can be integrated directly into packaging materials to provide continuous quality monitoring without altering the food itself (Saggin et al., 2019). This development extends RFID from identification to active environmental sensing, thereby enabling data driven food management systems.

In retail environments, RFID has long been used for inventory management, but recent advances have transformed it into a platform for real time location tracking, theft prevention, and customer behavior analysis. Systems based on RFID inventory networks, interference based localization, and neural driven gate control enable retailers to monitor item movement with unprecedented precision (Anssens et al., 2011; Liu et al., 2019; Alvarez Narciani et al., 2019). This spatial intelligence creates a digital twin of the physical store, allowing optimization of logistics, layout, and security.

Transportation systems, particularly in urban and highway contexts, have also been revolutionized by RFID. Electronic toll collection, vehicle identification, and traffic flow analysis rely on RFID based positioning and identification to support intelligent transportation infrastructures. Research by Lee et al. demonstrated early on that RFID and vehicle positioning systems could be integrated to enable automated tolling, while more recent studies have expanded this concept to include real time vehicular localization and lane monitoring (Lee et al., 2004; Zhang et al., 2019). These systems contribute not only to operational efficiency but also to road safety and environmental sustainability.

Despite this broad range of applications, the scientific literature on RFID remains fragmented across sensing, localization, communication, and regulatory domains. There is a need for an integrated theoretical framework that explains how these elements interact to form coherent Internet of Things systems. While individual studies have addressed specific components such as biopolymer sensors, angle of arrival localization, or convolutional neural networks for gate control, few have attempted to

synthesize these into a unified model of RFID based cyber physical intelligence. This article addresses this gap by constructing a comprehensive analytical narrative that connects physical layer materials, radio frequency propagation, signal processing, machine intelligence, and regulatory constraints into a single conceptual architecture.

The problem that motivates this research is not whether RFID can support IoT applications but how it can do so reliably, accurately, and at scale under real world constraints. Issues such as signal interference, multipath propagation, duty cycle regulations, synchronization, and extreme environment operation all impose limits on system performance (Saelens et al., 2019; Yildirim et al., 2019; Rashvand et al., 2014). Understanding how these constraints interact with sensing and localization algorithms is essential for designing robust RFID based IoT platforms. By drawing on a wide range of empirical and theoretical studies, this article develops a detailed understanding of these interactions and proposes a coherent framework for future research and deployment.

METHODOLOGY

The methodological approach adopted in this research is based on integrative theoretical synthesis combined with comparative analytical evaluation of existing empirical studies. Rather than introducing new experimental data, the objective is to extract, harmonize, and reinterpret the findings of authoritative RFID and Internet of Things research in order to build a comprehensive conceptual model. This approach is particularly appropriate in a field where rapid technological evolution has produced a large but fragmented body of knowledge across sensing, localization, communication, and regulatory analysis.

The first methodological step involves the categorization of RFID research into four interdependent layers: physical sensing, spatial localization, system level intelligence, and regulatory and operational constraints. Physical

sensing encompasses the materials, antennas, and integrated circuits that allow RFID tags to respond to environmental stimuli such as moisture, temperature, or chemical changes. Saggin et al. provided a detailed examination of how biopolymer based substrates can be engineered to change their electromagnetic response as food quality degrades, thereby enabling direct sensing through backscattered radio signals (Saggin et al., 2019). Similarly, Melia Segui and Vilajosana demonstrated how standard UHF RFID tags can be adapted to measure moisture levels in industrial contexts, showing that sensing does not require specialized electronics but can be achieved through clever manipulation of antenna properties (Melia Segui and Vilajosana, 2019). These studies form the empirical foundation of the sensing layer.

Spatial localization constitutes the second layer of analysis. Here, the methodology involves comparing different approaches to determining the position of RFID tags and objects using radio frequency measurements. Liu et al. developed an interference based three dimensional localization system capable of tracking both tagged and untagged targets, revealing how multipath interference, often considered a source of error, can be exploited as a source of spatial information (Liu et al., 2019). Xu et al. introduced support vector regression as a means of mapping received signal strength to physical coordinates, thereby incorporating machine learning into the localization pipeline (Xu et al., 2018). Zhou et al. focused on angle of arrival estimation, while Shao and Burkholder explored antenna spatial diversity as a means of improving item level location accuracy (Zhou et al., 2011; Shao and Burkholder, 2013). By synthesizing these approaches, the methodology identifies the fundamental trade offs between computational complexity, accuracy, and deployment cost.

The third layer, system level intelligence, examines how raw RFID data is transformed into actionable decisions. Alvarez Narciani et al. demonstrated how convolutional neural networks can process RFID gate data to classify object movement patterns,

enabling automated control systems for retail and logistics (Alvarez Narcandi et al., 2019). Farhat et al. explored advanced characterization of RFID items to enhance retail analytics, while Anssens et al. proposed network level architectures for RFID based inventory systems (Farhat et al., 2018; Anssens et al., 2011). In parallel, research on neural interfaces and backscattered communication protocols illustrates how RFID principles extend even into biomedical cyber physical systems, highlighting the generality of the underlying technology (Ranganathan et al., 2019; Arjona et al., 2019).

The final methodological layer addresses regulatory and environmental constraints. Saelens et al. analyzed how duty cycle and transmission power limits in European sub gigahertz bands affect low power wide area networks, which include many RFID based systems (Saelens et al., 2019). Yildirim et al. studied synchronization challenges in computational RFID networks, while Rashvand et al. reviewed wireless sensor systems for extreme environments, providing insight into the robustness required for industrial and transportation applications (Yildirim et al., 2019; Rashvand et al., 2014). Kranenburg and Bassi framed these issues within the broader context of IoT challenges, emphasizing scalability, interoperability, and sustainability (Kranenburg and Bassi, 2012).

By structuring the analysis around these four layers, the methodology enables a holistic understanding of how RFID based IoT systems operate. Each empirical study is interpreted not in isolation but as part of an interconnected technological ecosystem. The resulting synthesis forms the basis for the results and discussion that follow.

RESULTS

The integrated analysis of RFID based sensing and localization reveals a coherent pattern across diverse application domains. At the physical sensing level, the use of flexible and environmentally responsive materials fundamentally changes the role of RFID tags. Saggin et al. demonstrated that biopolymer

substrates can be engineered to exhibit changes in dielectric properties as food spoils, leading to measurable shifts in the backscattered signal that can be interpreted as indicators of quality (Saggin et al., 2019). This means that the RFID tag is no longer a passive identifier but an active sensor embedded directly into the product packaging. The result is a continuous, non invasive monitoring capability that aligns with the IoT vision of ubiquitous sensing.

Similarly, moisture sensing based on standard UHF RFID tags shows that even low cost off the shelf components can be repurposed as environmental sensors through careful antenna and substrate design (Melia Segui and Vilajosana, 2019). These findings collectively demonstrate that the sensing capacity of RFID is limited less by the integrated circuit and more by the electromagnetic interaction between the tag and its environment. This insight has profound implications for scalability, as it allows sensing to be deployed at the same scale as identification without significant cost increases.

In the domain of spatial localization, the results indicate that RFID can achieve surprisingly high accuracy when advanced signal processing techniques are applied. Interference based localization, as proposed by Liu et al., leverages the multipath nature of indoor radio propagation to create unique signal fingerprints that can be mapped to three dimensional positions (Liu et al., 2019). This approach challenges the traditional assumption that multipath is purely detrimental, instead revealing it as a rich source of spatial information. When combined with machine learning techniques such as support vector regression, these signal features can be translated into precise coordinate estimates even in complex environments (Xu et al., 2018).

Angle of arrival methods and antenna diversity further enhance localization performance by providing independent measurements of tag direction and signal strength (Zhou et al., 2011; Shao and Burkholder, 2013). The convergence of these techniques results in a multi dimensional localization framework that is robust to noise, occlusion, and tag

orientation. In retail and warehouse settings, this enables item level tracking that approaches the fidelity of much more expensive sensor systems.

The application of these localization capabilities to transportation systems yields significant operational benefits. RFID based vehicular localization allows traffic management systems to monitor vehicle movement, detect congestion, and enforce tolling and access control with minimal infrastructure. Zhang et al. demonstrated that RFID can be used not only to identify vehicles but also to estimate their position within the roadway network, enabling intelligent transportation systems that respond dynamically to real time conditions (Zhang et al., 2019). Belenguer et al. further showed that combining RFID with magnetic loops creates a hybrid sensing platform that enhances reliability and accuracy in vehicle identification (Belenguer et al., 2019). These results highlight the adaptability of RFID to outdoor and high speed environments, which were once considered beyond its capabilities.

At the system intelligence level, the integration of neural networks and advanced signal processing transforms raw RFID data into actionable insights. The convolutional neural network based gate control system proposed by Alvarez Narciani et al. exemplifies how machine learning can classify and predict object movement patterns from RFID signals, enabling automated decision making in retail and logistics (Alvarez Narciani et al., 2019). This approach reduces the need for rigid rule based systems and allows the infrastructure to adapt to changing patterns of behavior.

Retail analytics based on RFID item characterization and sensor networks further demonstrate how distributed RFID data can be aggregated into a comprehensive view of inventory and customer interaction (Farhat et al., 2018; Anssens et al., 2011). These systems support real time stock management, theft detection, and layout optimization, all of which contribute to operational efficiency and customer satisfaction.

The results also extend into biomedical and extreme environment applications, where backscattered communication and flexible protocols enable implantable and remote sensors to operate with minimal power and infrastructure (Ranganathan et al., 2019; Arjona et al., 2019). This reinforces the generality of RFID principles and their suitability for a wide range of IoT contexts.

Finally, the analysis of regulatory and operational constraints reveals that while RFID offers many advantages, it must operate within strict duty cycle, power, and synchronization limits. Saelens et al. showed that European duty cycle regulations impose significant constraints on transmission frequency and duration, which can affect the responsiveness of RFID based networks (Saelens et al., 2019). Yildirim et al. highlighted the importance of synchronization in computational RFID systems, where distributed tags must coordinate their communication to avoid collisions and ensure data integrity (Yildirim et al., 2019). Rashvand et al. emphasized the need for robust design in extreme environments, where temperature, radiation, and mechanical stress can degrade performance (Rashvand et al., 2014). These findings underscore the importance of holistic system design that accounts for both technological potential and regulatory reality.

DISCUSSION

The synthesis of RFID sensing, localization, and system intelligence reveals a technology that is far more versatile and powerful than its traditional perception as a simple identification tool. At a theoretical level, RFID represents a unique convergence of communication, sensing, and computation that aligns closely with the foundational vision of the Internet of Things articulated by Ashton and further developed by Jia and Feng (Ashton, 2009a; Jia et al., 2012). Unlike conventional sensor networks that require separate sensing, power, and communication subsystems, RFID integrates these functions into a single electromagnetic interaction between tag and reader. This integration creates opportunities for scalability and sustainability that

are unmatched by battery powered alternatives.

One of the most significant theoretical implications of the results is the reinterpretation of radio frequency phenomena such as multipath interference and backscatter modulation. Traditionally, these effects were treated as sources of noise that degrade communication quality. However, the work of Liu et al. and others demonstrates that these same phenomena can be exploited as rich sources of information about the environment and the position of objects within it (Liu et al., 2019). This shift from noise to signal represents a fundamental change in how wireless systems are conceptualized. It suggests that the complexity of the radio environment, rather than being an obstacle, can be harnessed as a computational resource.

The integration of machine learning into RFID localization and sensing further amplifies this potential. Support vector regression, convolutional neural networks, and other data driven models allow complex, nonlinear relationships between radio signals and physical states to be learned directly from data (Xu et al., 2018; Alvarez Narciani et al., 2019). This reduces the reliance on precise physical models, which are often difficult to obtain in cluttered and dynamic environments. At the same time, it raises important questions about generalization, robustness, and explainability. Machine learning models trained in one environment may not perform well in another, and their decisions may be difficult to interpret. Future research must address these issues to ensure that RFID based IoT systems remain reliable and trustworthy.

From a practical perspective, the application of RFID sensing and localization to food safety, retail, and transportation offers significant societal benefits. In the food supply chain, continuous quality monitoring can reduce waste, prevent foodborne illness, and improve consumer confidence (Saggin et al., 2019). In retail, real time inventory and movement tracking supports efficient operations and enhanced customer experiences (Farhat et al., 2018; Anssens et al., 2011). In transportation, RFID based

tolling and vehicle tracking contribute to smoother traffic flow, reduced congestion, and lower emissions (Lee et al., 2004; Zhang et al., 2019). These benefits align with broader goals of sustainability, safety, and economic efficiency.

However, the discussion must also acknowledge limitations and challenges. Regulatory constraints on duty cycle and transmission power impose hard limits on how frequently RFID systems can communicate, particularly in sub gigahertz bands used in many regions (Saelens et al., 2019). These limits can reduce the temporal resolution of sensing and localization, which may be problematic in fast changing environments such as traffic or industrial automation. Synchronization issues in large networks of computational RFID tags further complicate system design, as collisions and timing errors can lead to data loss and reduced accuracy (Yildirim et al., 2019).

Extreme environments present additional challenges. While RFID has been shown to operate in harsh conditions, factors such as temperature extremes, radiation, and mechanical stress can affect antenna performance and integrated circuit reliability (Rashvand et al., 2014). Designing tags and readers that can withstand these conditions without sacrificing cost and scalability remains an open research problem.

Looking to the future, the convergence of RFID with other IoT technologies such as low power wide area networks, edge computing, and digital twins promises to further expand its capabilities. Hybrid systems that combine RFID with magnetic loops, cameras, or other sensors can provide redundancy and enhance reliability, as demonstrated in vehicular identification systems (Belenguer et al., 2019). The integration of RFID data into cloud based analytics and control platforms will enable more sophisticated applications such as predictive maintenance, adaptive traffic management, and personalized retail experiences.

Ultimately, the theoretical and empirical evidence

reviewed in this article supports the conclusion that RFID based sensing and localization form a critical foundation for the next generation of Internet of Things systems. By embracing the complexity of radio frequency environments and leveraging advances in machine intelligence, these systems can achieve levels of performance and scalability that were once considered unattainable.

CONCLUSION

This research has presented a comprehensive synthesis of UHF RFID sensing and localization technologies within the broader context of the Internet of Things. Drawing on a wide range of authoritative studies, the article has demonstrated how RFID has evolved from a simple identification mechanism into a multifaceted platform for environmental sensing, spatial intelligence, and automated decision making. In food safety, flexible biopolymer based RFID sensors enable continuous quality monitoring at the level of individual packages. In retail, interference based localization, antenna diversity, and neural driven gate control systems create a real time digital representation of inventory and customer movement. In transportation, RFID based vehicular identification and localization support intelligent tolling, traffic management, and safety systems.

The theoretical implications of this evolution are profound. By reconceptualizing radio frequency phenomena as sources of information rather than noise, and by integrating machine learning into the signal processing pipeline, RFID based systems achieve a level of adaptability and robustness that aligns closely with the vision of ubiquitous computing. At the same time, regulatory, synchronization, and environmental constraints remind us that technological potential must be balanced with practical realities.

As the Internet of Things continues to expand, the role of RFID is likely to grow rather than diminish. Its unique combination of low power operation, scalability, and integration of sensing and

communication makes it an indispensable component of future cyber physical infrastructures. The challenge for researchers and practitioners is to continue refining the theoretical models, algorithms, and materials that underpin these systems, ensuring that they remain reliable, secure, and beneficial to society.

REFERENCES

1. Alvarez Narciani, G.; Motroni, A.; Pino, M.R.; Buffi, A.; Nepa, P. A UHF RFID gate control system based on a convolutional neural network. In Proceedings of the IEEE International Conference on RFID Technology and Applications, Pisa, Italy, 25 to 27 September 2019; pp. 353 to 356.
2. Anssens, C.; Rolland, N.; Rolland, P. A sensor network based on RFID inventory for retail application. In Proceedings of the IEEE International Conference on RFID Technologies and Applications, Sitges, Spain, 15 to 16 September 2011; pp. 64 to 67.
3. Arjona, L.; Rosenthal, J.; Smith, J.R.; Moritz, C.T. High performance flexible protocol for backscattered based neural implants. In Proceedings of the IEEE APS Topical Conference on Antennas and Propagation in Wireless Communications, Granada, Spain, 9 to 13 September 2019; pp. 276 to 280.
4. Ashton, K. That internet of things thing. RFID Journal, 2009a, 22, 97 to 114.
5. Ashton, K. In the real world, things matter more than ideas. RFID Journal, 2009b.
6. Belenguer, F.M.; Martinez Millana, A.; Salcedo, A.M.; Nunez, J.H.A. Vehicle identification by means of radio frequency identification cards and magnetic loops. IEEE Transactions on Intelligent Transportation Systems, 2019, 1 to 9.
7. Farhat, H.; Iliev, P.; Marriage, P.; Rolland, N. An added value alternative to RAIN RFID items

- characterization in retail. *IEEE Access*, 2018, 6, 32430 to 32439.
8. Jia, X.; Feng, Q.; Fan, T.; Lei, Q. RFID technology and its applications in Internet of Things. In *Proceedings of the International Conference on Consumer Electronics, Communications and Networks*, IEEE, 2012; pp. 1282 to 1285.
 9. Kranenburg, V.; Bassi, A. IoT challenges. *Communications in Mobile Computing*, 2012, 1, 1 to 5.
 10. Lee, W.H.; Jeng, B.S.; Tseng, S.S.; Wang, C.H. Electronic toll collection based on vehicle positioning system techniques. In *Proceedings of the IEEE International Conference on Networking, Sensing, and Control*, Taipei, Taiwan, 21 to 23 March 2004; pp. 643 to 648.
 11. Liu, M.; Wang, H.; Yang, Y.; Zhang, Y.; Ma, L.; Wang, N. RFID three dimensional indoor localization for tag and tag free target based on interference. *IEEE Transactions on Instrumentation and Measurement*, 2019, 68, 718 to 732.
 12. Melia Segui, J.; Vilajosana, X. Ubiquitous moisture sensing in automaker industry based on standard UHF RFID tags. In *Proceedings of the IEEE International Conference on RFID*, Phoenix, AZ, USA, 2 to 4 April 2019; pp. 1 to 8.
 13. Ranganathan, V.; Nakahara, J.; Samejima, S.; Tolley, N.; Khorasani, A.; Moritz, C.T.; Smith, J.R. NeuralCLIP a modular FPGA based neural interface for closed loop operation. In *Proceedings of the International IEEE EMBS Conference on Neural Engineering*, San Francisco, CA, USA, 20 to 23 March 2019; pp. 791 to 794.
 14. Rashvand, H.F.; Abedi, A.; Alcaraz Calero, J.M.; Mitchell, P.D.; Mukhopadhyay, S.C. Wireless sensor systems for space and extreme environments a review. *IEEE Sensors Journal*, 2014, 14, 3955 to 3970.
 15. Saelens, M.; Hoebeke, J.; Shahid, A.; De Poorter, E. Impact of EU duty cycle and transmission power limitations for sub GHz LPWAN SRDs an overview and future challenges. *EURASIP Journal on Wireless Communications and Networking*, 2019, 219.
 16. Saggin, B.; Belaizi, Y.; Vena, A.; Sorli, B.; Guillard, V.; Dedieu, I. A flexible biopolymer based UHF RFID sensor for food quality monitoring. In *Proceedings of the IEEE International Conference on RFID Technology and Applications*, Pisa, Italy, 25 to 27 September 2019; pp. 484 to 487.
 17. Shao, S.; Burkholder, R.J. Item level RFID tag location sensing utilizing reader antenna spatial diversity. *IEEE Sensors Journal*, 2013, 13, 3767 to 3774.
 18. Valhouli, C.A. The Internet of Things networked objects and smart devices. The Hammersmith Group Research Report, 2010, 20.
 19. Xu, H.; Wu, M.; Li, P.; Zhu, F.; Wang, R. An RFID indoor positioning algorithm based on support vector regression. *Sensors*, 2018, 18, 1504.
 20. Yildirim, K.S.; Aantjes, H.; Pawelczak, P.; Majid, A.Y. On the synchronization of computational RFIDs. *IEEE Transactions on Mobile Computing*, 2019, 18, 2147 to 2159.
 21. Zhang, Y.; Ma, Y.; Liu, K.; Wang, J.; Li, S. RFID based vehicular localization for intelligent transportation systems. In *Proceedings of the IEEE International Conference on RFID Technology and Applications*, Pisa, Italy, 25 to 27 September 2019; pp. 267 to 272.
 22. Zhou, J.; Zhang, H.; Mo, L. Two dimension localization of passive RFID tags using AOA estimation. In *Proceedings of the Instrumentation and Measurement Technology*

Conference, Beijing, China, 10 to 12 May 2011;
pp. 1 to 5.